



GasAlert MicroClip

multi-gas detector



Multi-gas made simple

The slim and compact GasAlertMicroClip provides affordable protection from atmospheric hazards. With simple one-button operation, this multi-gas detector offers ultimate ease of use and significantly reduces time spent training the user. The GasAlertMicroClip is fully compatible with BW's MicroDock II automatic test and calibration system.



H₂S
CO
O₂
LEL

- Multi-gas versatility with one-button simplicity
- Incredibly thin and lightweight, making it comfortable to wear
- Extraordinarily low cost of ownership




**WATER
RESISTANT** 

BW
Technologies
by Honeywell

Wear yellow. Work safe.

Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

GasAlertMicroClip Specifications		
Size	4.2 x 2.4 x 1.1 in. / 10.8 x 6.0 x 2.7 cm	
Weight	5.7 oz. / 160 g	
Temperature	-4 to +136°F / -20 to +58°C	
Humidity	0% - 95% RH (non-condensing)	
Alarms	- Visual, vibrating, audible (95dB) - Low, High, STEL, TWA, OL (over limit)	
Tests	Audible/visual alarms on activation, sensors, battery and circuitry (continuous)	
Pump	Compatible with the Sampler motorized sampling pump	
Typical battery life	12 hours (typical); recharges in less than 3 hours	
User options	Confidence beep	Combustible gas measurement (% LEL or % by volume methane)
	Set STEL interval	User-settable calibration gas level
	Sensor on/off	Force bump test when overdue
	Latching alarms	Force calibration when overdue
	Safe display mode	Low alarm acknowledge
	Stealth mode	Language choices (5)
	Calibration lock	Set custom start up message
	Auto zero on start up	
	O ₂ auto calibration on start up	
	Set bump test interval	
Ratings	EMI/RFI: Complies with EMC Directive 89/336/EEC IP 65/67	
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D  American Bureau of Shipping ATEX:  II 1 G T4 Ex ia IIC T4 IECEX: Ex ia IIC T4 CE: European Conformity	
Warranty	Full 2 year warranty including all sensors	

Additional GasAlertMicroClip features:

- Tamper-proof, one button operation
- Compatible with the Sampler motorized remote sampling pump
- Equipped with internal vibrating alarm for high noise areas
- Powered by a lithium polymer battery
- Multi-language support in English, French, German, Spanish and Portuguese
- Conveniently manage your fleet using Soft Tools

Options and Accessories



MicroDock II compatible



Auxillary Filter Kit



IR Connectivity Kit



Five unit Cradle Charger


For a complete list of accessories, please contact BW Technologies.

Sensor Specifications

Gas	Measuring Range	Resolution
H₂S	0-100 ppm	1 ppm
CO	0-500 ppm	1 ppm
O₂	0-30.0%	0.1%
Combustible gases	0-100% LEL 0-5.0% v/v	1% 0.1%

Alarm set points for all sensors are user adjustable. Set point(s) are automatically displayed during instrument start up.

Locally available from



DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



For customer service, call 1300-735-295
 Email InfoGasAU@thermofisher.com
 Visit us online: www.thermofisher.com.au

©2010 Thermo Fisher Scientific Inc. All rights reserved. A.B.N. 52 058 390 917